

Hole		From (m)	To (m)	Length (m)	% V2O5	% Cu
C-04		2.0	24.7	22.7	0.240	
	including	7.1	17.0	9.9	0.301	
	and	56.8	59.8	3.0	0.220	
C-05		4.3	12.0	7.8	0.305	
C-06		7.1	15.2	8.1	0.193	0.11
	and	18.4	22.3	3.9	0.257	
	and	50.9	64.0	13.1	0.199	
C-07		12.0	15.1	3.1	0.242	
	and	23.4	46.6	23.2	0.166	
	including	38.3	44.2	5.9	0.206	
C-09		3.4	61.0	57.6	0.176	
	including	25.0	39.1	14.1	0.219	
C-10		1.8	16.4	14.5	0.192	0.08
	including	8.8	11.8	3.0	0.300	0.19
		64.0	78.0	14.0	0.171	
C-11		12.0	55.0	43.0	0.197	
	including	32.0	40.0	8.0	0.326	0.18
		79.0	85.0	6.0	0.165	
C-12		75.3	84.5	9.2	0.246	
C-13		7.2	24.4	17.2	0.209	
	including	18.0	22.4	4.4	0.330	
		33.0	37.0	4.0	0.250	
		41.0	47.8	6.9	0.168	
C-14		8.0	70.6	62.6	0.237	
	including	12.1	27.1	15.0	0.301	0.13
	and	31.3	36.6	5.4	0.335	0.10
		98.5	101.5	3.0	0.210	
C-15		41.1	55.4	14.3	0.212	
C-17		26.0	36.8	10.8	0.211	0.15
		70.0	76.0	6.0	0.196	
		104.0	114.0	10.0	0.165	
C-19		70.7	80.0	9.4	0.227	0.143
C-22		63.7	69.7	6.0	0.170	

Hole		From (m)	To (m)	Length (m)	% V2O5	% Cu
C-23		72.0	75.0	3.0	0.271	
		81.6	83.6	2.0	0.164	
C-31		49.0	53.8	4.8	0.174	
		61.1	74.0	13.0	0.163	
C-32		24.0	67.0	43.0	0.278	
	including	30.0	40.0	10.0	0.369	
	and	48.5	52.0	3.4	0.371	
	and	59.2	65.0	5.8	0.330	
		72.3	76.0	3.8	0.170	
	88.0	94.0	6.0	0.334		
ML-01		46.3	55.1	8.8	0.229	
	including	46.6	50.4	3.8	0.344	
ML-15		54.1	69.6	15.5	0.305	
	including	63.2	67.6	4.4	0.450	
		88.1	94.4	6.4	0.181	
ML-16		57.1	64.9	7.8	0.163	
		88.4	92.0	3.7	0.310	
		100.0	106.9	6.9	0.205	
ML-17		61.7	79.0	17.3	0.184	
	including	61.7	69.0	7.3	0.227	
		97.3	104.4	7.2	0.153	
		111.6	117.8	6.2	0.233	
ML-21		51.2	80.7	29.5	0.194	
		84.7	100.2	15.5	0.193	
ML-50		68.2	114.0	45.9	0.183	
	including	68.2	87.0	18.9	0.216	
ML-57		21.2	61.2	40.0	0.228	
	including	27.2	30.2	3.0	0.302	
	and	38.7	44.2	5.5	0.334	0.10
	and	48.2	52.2	4.0	0.312	
	63.0	68.0	5.0	0.191	0.11	
ML-58		33.0	35.5	2.5	0.257	
		108.1	115.6	7.5	0.178	

Hole	From (m)	To (m)	Length (m)	% V2O5	% Cu
ML-59 including and	27.0	102.0	75.0	0.231	
	28.0	33.0	5.0	0.317	0.09
	73.6	80.6	7.0	0.407	
ML-61	139.0	171.0	32.0	0.167	
ML-63 including	77.7	82.4	4.7	0.152	0.14
	160.3	222.0	61.7	0.176	
	161.0	170.0	9.0	0.292	0.26
ML-73	124.5	127.0	2.5	0.191	
	178.0	198.0	20.0	0.199	
	206.0	247.0	40.8	0.195	
	253.0	285.3	32.3	0.179	
ML-74	176.0	249.0	73.0	0.163	
ML-81	1.6	38.0	36.4	0.165	
ML-83	3.0	42.5	39.5	0.178	
ML-108*	14.4	40.0	25.6	0.160	
	72.0	126.6	54.6	0.214	
ML-111	3.0	46.4	43.4	0.153	
ML-112	1.7	53.6	51.9	0.171	
ML-114 including	192.0	264.0	72.0	0.209	
	196.0	202.0	6.0	0.337	
	278.0	290.0	12.0	0.164	
	356.0	357.6	1.6	0.364	
	373.0	377.0	4.0	0.196	
ML-129*	18.5	48.0	29.5	0.184	
	19.5	28.0	8.5	0.237	
ML-143 including	94.0	98.0	4.0	0.157	
	114.0	128.0	14.0	0.331	
	118.0	122.0	4.0	0.428	
ML-151*	4.0	64.0	60.0	0.161	
ML-152	75.0	77.0	2.0	0.291	
ML-156	7.3	15.0	7.8	0.185	

Hole	From (m)	To (m)	Length (m)	% V2O5	% Cu
ML-162	5.0	29.0	24.0	0.169	
	51.0	48.0	7.0	0.222	
	58.0	90.0	32.0	0.162	
	97.0	101.0	4.0	0.160	
	104.0	107.0	3.0	0.165	
	114.0	117.0	3.0	0.220	
ML-163*	39.00	64.0	25.0	0.346	
	39.0	52.0	13.0	0.490	
ML-170*	2.3	38.0	35.7	0.218	
	20.0	28.0	8.0	0.318	
ML-171*	1.4	29.0	27.6	0.231	
ML-172*	2.0	30.0	28.0	0.168	
ML-178	7.0	13.0	5.0	0.159	
	26.0	36.0	10.0	0.174	
ML-179	5.0	9.0	4.0	0.186	
	25.0	36.0	11.0	0.215	
	62.0	98.0	36.0	0.182	
	120.0	134.0	14.0	0.164	
	158.0	162.0	4.0	0.200	
	190.0	198.0	8.0	0.177	
	205.0	215.0	10.0	0.178	
227.0	235.0	8.0	0.186		
ML-181	14.0	21.5	7.5	0.184	
	33.0	36.5	3.5	0.186	
	58.5	213.5	155.0	0.184	
	including	65.5	98.5	33.0	0.216
ML-182	30.0	271.0	241.0	0.179	
	including	48.0	60.0	12.0	0.203
	and	74.0	84.0	10.0	0.203
	and	120.0	130.0	10.0	0.244
	and	158.0	168.0	10.0	0.249
	and	204.0	224.0	20.0	0.228

* Newly released holes

** Composites based on a 0.15% V2O5 cutoff grade